

Cutter Bar Lubricant Range

Technical Data Sheet

PRODUCT DESCRIPTION

Müller Lubrication Cutter Bar Lubricant Range is recommended for the lubrication of cutting chains, cutter bars and drive gear on hand-held chain saws. The oil contains an exceptional tackiness additive pack to ensure that adequate lubricant adheres to the rubbing surfaces of this total loss system.

Designed for the lubrication of stationary power saws and cutting equipment. An ideal product for industrial applications where a contact between equipment and the surrounding natural world is inevitable. Enhanced lubricity and improved tackiness define it particularly suitable for use on hot summer days.

TYPICAL TECHNICAL CHARACTERISTICS

DESCRIPTION	RESULT	TEST METHOD
Density at 15°C	kg/m ³	ISO 12185
Kinematic Viscosity cSt @ 40°C	mm ² /s	ASTM D445
Pour Point	°C	ASTM D97
Flash Point, COC	°C	ASTM D92
Steel corrosion at 100°C/3h		
Biodegradability (within 21 days)	%	OECD 301B

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

PACKAGING

- 500ml Bottle
- 1 Litre Bottle
- 5 Litre Bottle
- 20 Litre Pail
- 210 Litre Drum
- 1 000 Litre IBC

Misrepresentation Act 1967. Trade description Act 1968. The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason no warranty is given, express or implied. This information sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.