

## General Purpose Grease

### Technical Data Sheet

#### PRODUCT DESCRIPTION

General purpose EP2 grease.

#### PRODUCT DESCRIPTION

- Multi-purpose application in both industrial and automotive fields.
- No Drop Point and high operating-temperature capability.
- Long life relative to conventional grease.
- Excellent EP and anti-wear properties.
- Low oil-separation characteristics.
- Excellent corrosion resistance and high shear capability.

#### TYPICAL TECHNICAL CHARACTERISTICS

DESCRIPTION	RESULT	TEST METHOD
Product Code	GP100	
NLGI Classification	2/3	IP 50*
Thickener	Proprietary	
Texture	Smooth	FLM 212*
Colour	Dark Brown	FLM 212*
Base Oil Viscosity at 40 °C mm <sup>2</sup> /s	1000 (Bright stock)	
Drop Point	Non drop	IP 396*
Worked Penetration 60 strokes @ 25°C	245	IP 50*
Timken OK Load	21	ASTM D2509*
Scar diameter	0.71mm	ASTM D2266-01 R2008*
Weld point	250kgf	ASTM D2596-15*
Cone Penetration	245mm/10	IP 50*

\*Test results as per August 2021 tests by Intertek UK grease testing facility. The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

#### PACKAGING

- 15kg Steel Pails
- 18kg Plastic Pails
- 50kg Steel Drums
- 180kg Steel Open Top Drums

The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason no warranty is given, express or implied. This information sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Misrepresentation Act 1967. Trade description Act 1968.