



14 Trafford Road, Pinetown, Durban, 3610  
(031) 700 9009 / 063 325 1829 / 083 378 5751  
info@mullerlubes.co.za / gavin@mullerlubes.co.za  
www.mullerlubrication.co.za

## 15W-40 SL/CI4 Nextgen

### Technical Data Sheet

#### PRODUCT DESCRIPTION

Müller Lubrication 15W-40 SL/CI4 Nextgen is an extra high performance diesel engine oil that provides excellent lubrication of today's diesel engines promoting extended engine life. This extra high performance oil has been proven in the field in a wide variety of industries, applications, and mixed fleets.

#### FEATURES

Müller Lubrication 15W-40 SL/CI4 Nextgen is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in modern diesel and gasoline engines as well as older models.

#### KEY BENEFITS

- High thermal and oxidation stability.
- Reduced sludge build-up.
- Deposit control and acid neutralisation.
- Stay-in-grade shear stability.
- Wear protection and viscosity control.
- Advanced detergency/dispersancy.
- Cleaner engines and longer component life.
- Improved soot handling, viscosity control and used oil pumpability.
- Excellent low temperature properties.
- Start-up wear protection.
- Component compatibility.
- Longer gasket and seal life.
- Maximum soot handling and excellent wear protection.
- Improved engine cleanliness.
- Combats contaminants resulting in longer drain intervals.

#### TYPICAL TECHNICAL CHARACTERISTICS

DESCRIPTION	RESULT
SAE No.	15W-40 SL/CI4
Viscosity cSt @ 40°C	110
Viscosity cSt @ 100°C	14.8
Viscosity Index	140
Flash Point, °C	230
Pour Point, °C	-39
Total Base No., mgKOH/g	10

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

#### PERFORMANCE STANDARDS

- API CI-4/SL
- ACEA E3/B4
- JASO DH-1 (Level)
- VOLVO VDS-3
- MACK EO-N/EO-M Plus
- MACK EO-N/EO-M Plus
- Renault RLD-2
- MAN M3275
- MTU Type 2
- Detroit Diesel DDC 93K215
- CAT ECF 1a/2
- Cummins CES 20076/77/78
- DEUTZ DQC III-10
- GLOBAL DHD-1
- ALLISON TES 493
- MB 228.3 / 229.1

## PACKAGING

- 1 Litre Bottle
- 5 Litre Bottle
- 20 Litre Pail
- 210 Litre Drum
- 1 000 Litre IBC

The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason no warranty is given, express or implied. This information sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Misrepresentation Act 1967. Trade description Act 1968.