

Universal Super Agri Farm Oil

Technical Data Sheet

PRODUCT DESCRIPTION

Müller Lubrication Universal Super Agri Farm Oil is a premium mineral Super Tractor Oil Universal (STOU) manufactured from highly refined base oils and advanced multi-functional additives. It is a multi purpose product for use in a wide range of machines and covers multiple applications.

FEATURES

Anti-wear and oxidation stability. Proven protection of critical parts.

TYPICAL TECHNICAL CHARACTERISTICS

DESCRIPTION	RESULT
Density at 15°C, kg/L	0.871
Kinematic Viscosity cSt @ 40°C	100
Kinematic Viscosity cSt @ 100°C	14
Viscosity Index	142
Cold Cranking Viscosity, cP at 20°C	4767
Zinc, Mass %	0.139

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

PERFORMANCE STANDARDS

- ACEA: E3
- ALLISON: C4 (Agriculture applic.)
- API: CG-4
- API GL-4
- API: GL-5 (Low speed/high torque)
- API: SF/CE
- CASE: MAT 3525
- CASE: MAT 3526
- EATON VICKERS: M-2950-S
- FORD: ESN-M2C134 C/D
- FORD: ESN-M2C159 B/C
- FORD: FNH 82009203
- JD: J20C
- JD: J27

PACKAGING

- 1 Litre Bottle
- 5 Litre Bottle
- 20 Litre Pail
- 210 Litre Drum
- 1 000 Litre IBC

The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason no warranty is given, express or implied. This information sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Misrepresentation Act 1967. Trade description Act 1968.